

Version 1.10 Revision Date 01/26/2015 SDS Number 300000000099 Print Date 03/07/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Nitrogen

Chemical formula : N2

Synonyms : Nitrogen, Nitrogen gas, Gaseous Nitrogen, GAN

Product Use Description : General Industrial

Manufacturer/Importer/Distribu

tor

: Air Products and Chemicals, Inc

7201 Hamilton Blvd.

Allentown, PA 18195-1501 GST No. 123600835 RT0001 QST No. 102753981 TQ0001

Telephone : 1-610-481-4911 Corporate

1-800-345-3148 Chemicals Cust Serv 1-800-752-1597 Gases/Electronics Cust Serv

Emergency telephone number : 800-523-9374 USA

(24h) +1 610 481 7711 International

2. HAZARDS IDENTIFICATION

GHS classification

Gases under pressure -

Compressed gas.

Simple Asphyxiant GHS label elements

Hazard pictograms/symbols



Signal Word: Warning

Hazard Statements:

H280:Contains gas under pressure; may explode if heated.

Version 1.10

Revision Date 01/26/2015

SDS Number 300000000099 Print Date 03/07/2015

May displace oxygen and cause rapid suffocation.

Precautionary Statements:

Storage : P410+P403:Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise classified

High pressure gas.

Can cause rapid suffocation.

Self contained breathing apparatus (SCBA) may be required.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Concentration (Volume)
Nitrogen	7727-37-9	100 %

Concentration is nominal. For the exact product composition, please refer to Air Products technical specifications.

4. FIRST AID MEASURES

General advice : Remove victim to uncontaminated area wearing self contained breathing

apparatus. Keep victim warm and rested. Call a doctor. Apply artificial

respiration if breathing stopped.

Eye contact : Not applicable.

Skin contact : Not applicable.

Ingestion : Ingestion is not considered a potential route of exposure.

Inhalation : Remove to fresh air. If breathing has stopped or is labored, give assisted

respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. In

case of shortness of breath, give oxygen.

Most important

symptoms/effects - acuate

and delayed

Exposure to oxygen deficient atmosphere may cause the following symptoms:

Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : All known extinguishing media can be used.

Specific hazards : Upon exposure to intense heat or flame, cylinder will vent rapidly and or rupture

2/9

Version 1.10 Revision Date 01/26/2015 SDS Number 300000000099 Print Date 03/07/2015

violently. Product is nonflammable and does not support combustion. Move away from container and cool with water from a protected position. Keep containers and surroundings cool with water spray. Most cylinders are designed to vent contents when exposed to elevated temperatures.

Special protective equipment for fire-fighters

: Wear self contained breathing apparatus for fire fighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures : Evacuate personnel to safe areas. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Monitor oxygen level. Ventilate the area.

Environmental precautions

: Do not discharge into any place where its accumulation could be dangerous.

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

: Ventilate the area.

Additional advice

If possible, stop flow of product. Increase ventilation to the release area and monitor oxygen level. If leak is from cylinder or cylinder valve, call the Air Products emergency telephone number. If the leak is in the user's system, close the cylinder valve and safely vent the pressure before attempting repairs.

7. HANDLING AND STORAGE

Handling

Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C (122°F). Only experienced and proper ly instructed persons should handle compressed gases/cryogenic liquids. Before using the product, determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Use an adjustable strap wrench to remove over-tight or rusted caps. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction. Ensure the complete gas system has been checked for leaks before use. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing a leak to occur. Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Close valve after each use and when empty. Replace outlet caps or plugs and container caps as soon as container is disconnected from equipment. Do not subject containers to abnormal mechanical shock. Never attempt to lift a cylinder by its valve protection cap or quard. Do not use containers as rollers or supports or for any other purpose than to contain the gas as supplied. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit. Do not smoke while handling product

Version 1.10 Revision Date 01/26/2015

SDS Number 300000000099 Print Date 03/07/2015

or cylinders. Never re-compress a gas or a gas mixture without first consulting the supplier. Never attempt to transfer gases from one cylinder/container to another. Always use backflow protective device in piping. When returning cylinder install valve outlet cap or plug leak tight. Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C (122° F).

Storage

Open/close valve slowly. Close when not in use. Wear Safety Eye Protection. Check Safety Data Sheet before use. Use a back flow preventative device in the piping. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Read and follow the Safety Data Sheet (SDS) before use. Full containers should be stored so that oldest s tock is used first. Containers should be stored in a purpose build compound which should be well ventilated, preferably in the open air. Stored containers should be periodically checked for general condition and leakage. Observe all regulations and local requirements regarding storage of containers. Protect containers stored in the open against rusting and extremes of weather. Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged. Container valve guards or caps should be in place. Keep containers tightly closed in a cool, well-ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Full and empty cylinders should be segregated. Do not allow storage temperature to exceed 50°C (122°F). Return empty containers in a timely manner.

Technical measures/Precautions

Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) and in accordance whit local regulations. Keep away from combustible material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures

Provide natural or mechanical ventilation to prevent oxygen deficient atmospheres below 19.5% oxygen.

Personal protective equipment

Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with

mask are to be used in oxygen-deficient atmosphere.

Air purifying respirators will not provide protection. Users of breathing

apparatus must be trained.

Hand protection : Wear working gloves when handling gas containers.

Chemical-resistant, impervious gloves complying with an approved standard

should be worn at all times when handling chemical products if a risk

assessment indicates this is necessary.

Eye protection : Safety glasses recommended when handling cylinders.

Skin and body protection : Safety shoes are recommended when handling cylinders.

Special instructions for protection and hygiene

: Ensure adequate ventilation, especially in confined areas.

Version 1.10 Revision Date 01/26/2015 SDS Number 300000000099 Print Date 03/07/2015

Remarks : Simple asphyxiant.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Compressed gas. Colorless gas

Odor : No odor warning properties.

Odor threshold : No data available.

pH : Not applicable.

Melting point/range : $-346 \ \mbox{\ensuremath{\upred}{\ensuremath{\ensuremath{\upred}{\ensuremath{\upred}{\ensuremath{\ensuremath{\upred}{\ensuremath{\ensuremath{\upred}{\ensuremath{$

Flash point : Not applicable.

Evaporation rate : Not applicable.

Flammability (solid, gas) : Refer to product classification in Section 2

Upper/lower

explosion/flammability limit

: No data available.

Vapor pressure : Not applicable.

Water solubility : 0.02 g/l

Relative vapor density : 0.97 (air = 1) Lighter or similar to air.

Relative density : No data available.

Partition coefficient (n-

octanol/water)

: Not applicable.

Auto-ignition temperature : No data available.

Decomposition temperature : No data available.

Viscosity : Not applicable.

Molecular Weight : 28 g/mol

Density : 0.075 lb/ft3 (0.0012 g/cm3) at 70 \uppi (21 \uppi) Note: (as vapor)

Specific Volume : 13.80 ft3/lb (0.8615 m3/kg) at 70 \uppi (21 \uppi)

Version 1.10 Revision Date 01/26/2015 SDS Number 300000000099 Print Date 03/07/2015

10. STABILITY AND REACTIVITY

Chemical Stability : Stable under normal conditions.

Conditions to avoid No data available.

Materials to avoid Hazardous decomposition

products

Possibility of hazardous Reactions/Reactivity

No data available. : No data available.

: No data available.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Likely routes of exposure

Effects on Eye : No adverse effect.

Effects on Skin : No adverse effect.

Inhalation Effects : In high concentrations may cause asphyxiation. Asphyxiation may bring about

unconsciousness without warning and so rapidly that victim may be unable to

protect themselves.

Ingestion Effects : Ingestion is not considered a potential route of exposure.

Symptoms Exposure to oxygen deficient atmosphere may cause the following symptoms:

Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

Acute toxicity

Acute Oral Toxicity : No data is available on the product itself.

Inhalation : No data is available on the product itself.

: No data is available on the product itself. **Acute Dermal Toxicity**

Skin corrosion/irritation : No data available.

Serious eye damage/eye

irritation

: No data available.

Sensitization. : No data available.

Chronic toxicity or effects from long term exposures

Carcinogenicity : No data available.

Version 1.10 Revision Date 01/26/2015 SDS Number 300000000099 Print Date 03/07/2015

Reproductive toxicity : No data is available on the product itself.

Germ cell mutagenicity : No data is available on the product itself.

Specific target organ systemic

toxicity (single exposure)

: No data available.

Specific target organ systemic

toxicity (repeated exposure)

: No data available.

Aspiration hazard : No data available.

Delayed and Immediate Effects and Chronic Effects from Short and Long Term Exposure

Not applicable.

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Aquatic toxicity : No data is available on the product itself.

Toxicity to other organisms : No data available.

Persistence and degradability

Biodegradability : No data is available on the product itself.

Mobility : No data available.

Bioaccumulation : No data is available on the product itself.

Further information

No ecological damage caused by this product.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused

products

 $: \ \, \hbox{Contact supplier if guidance is required. Return unused product in original} \\$

cylinder to supplier.

Contaminated packaging : Return cylinder to supplier.

14. TRANSPORT INFORMATION

Version 1.10 Revision Date 01/26/2015 SDS Number 300000000099 Print Date 03/07/2015

DOT

UN/ID No. : UN1066

Proper shipping name : Nitrogen, compressed

Class or Division : 2.2 Label(s) : 2.2 Marine Pollutant : No

IATA

UN/ID No. : UN1066

Proper shipping name : Nitrogen, compressed

Class or Division : 2.2 Label(s) : 2.2 Marine Pollutant : No

IMDG

UN/ID No. : UN1066

Proper shipping name : NITROGEN, COMPRESSED

Class or Division : 2.2 Label(s) : 2.2 Marine Pollutant : No

TDG

UN/ID No. : UN1066

Proper shipping name : NITROGEN, COMPRESSED

Class or Division : 2.2 Label(s) : 2.2 Marine Pollutant : No

Further Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact an Air Products customer service representative.

15. REGULATORY INFORMATION

Toxic Substance Control Act (TSCA) 12(b) Component(s):

None.

Country	Regulatory list	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	Included on Inventory.

Version 1.10 Revision Date 01/26/2015 SDS Number 300000000099 Print Date 03/07/2015

Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.
Japan	ENCS	Included on Inventory.

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification Sudden Release of Pressure Hazard.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

16. OTHER INFORMATION

NFPA Rating

Health : 0
Fire : 0
Instability : 0
Special : SA

HMIS Rating

Health : 0 Flammability : 0 Physical hazard : 3

Prepared by : Air Products and Chemicals, Inc. Global EH&S Product Safety Department

Telephone : 1-610-481-4911 Corporate

1-800-345-3148 Chemicals Cust Serv

1-800-752-1597 Gases/Electronics Cust Serv

Preparation Date : 03/07/2015

For additional information, please visit our Product Stewardship web site at http://www.airproducts.com/productstewardship/